# Managing Multi-Site, Multi Technology Connectivity



SQUARE MILE SYSTEMS

## Why Manage Connectivity?

- Increase in project costs and delays
  - Reverse engineering with workshops, site surveys, etc.
  - Overloading of key engineers / individuals
- Increased risks
  - The "human factor" (guess, assume, worry, forget, etc.)
  - Huge security holes
- Transformation activities are costly
  - Upgrading networks, consolidation, cloud migration

Physical connectivity data highlights the current understanding of inventory and dependency.

<u>An easy target for auditors!</u>



## Overview






- Understand the Problem(s)
- Standards can help or hinder
- New technology challenges
- Organisational challenges
- Labelling not the same as naming
- Case Study(s)

## A Starting Point?


- 1. Is every device in data center / equipment rooms and how it is connected currently documented in a common system that supports connectivity for both planning and operations needs?
  - Data, power, video, voice, building management, CCTV
- 2. Are change updates to inventory and connectivity data duplicated in spreadsheets, diagrams and databases in a consistent way?
  - When devices are added / changed / removed
  - With changes in backbone cabling or patching
- 3. Can you create detailed work packages for connectivity changes for internal or external engineers, without visiting site beforehand, or being there during changes?
- 4. Does current connectivity documentation for data centers and shared equipment rooms use consistent naming conventions across all locations, devices and connections?

# Information Requirements Force Technical Change



Infrastructure responds to change so there are limits to what you can manage

## How Do We Cope?



- Adopt industry best practices where they exist
- Ensure operational processes are not the weakest link
  - Ensure clarity on roles and practices
- Make the complexity easier to manage
  - Clear naming, labelling and documentation
  - Reduce the number of data sets needed for governance and control

## Case Study One

#### Two data centers (co-lo)

- approx 400 racks
- 36200 fiber/copper connections
- 5800 patches
- 600 servers




## "I'm just overloaded and can't get others to understand

4 spreadsheets – inventory + connectivity per DC (>1.8 million cells) + >6000 other spreadsheets

Maintained by <u>a</u> data center manager – no onsite staff


# Requesting a Connection -1



Device 1	Port	Connection	Port	Device 2
SW-BHAM-09	23	To be filled in by DC team	NIC 1	UK_BIRM_BLADE- 03

This is the initial spreadsheet used to capture connectivity requests


# Requesting a Connection -2



Device 1	Port	Connection	Port	Device 2
SW-BHAM-09	23	To be filled in by DC team	NIC 1	UK_BIRM_BLADE- 03
Room Rack Position Make Model Asset Number IP Address	Port Type Speed VLAN	Colour Cable Label Connection type Length	Port Type Speed VLAN	Room Rack Position Make Model Asset Number IP Address

The spreadsheet just went from 4 to 30 columns wide!

# Naming & Labelling



## Ports and Connections


## Equipment – use the physical label?

#### Port name


- 1 or 01 or 001?
- 2/1 2\1 2/01 SL2/1 Port 2/1 Gig 2/1 Fe2/1 Slot 2/09
- Mgmt MGT Con Console ILO Net Mgmt
- NIC 1 Eth A Net o hbao bge1 12F1 primary

#### **Cable Labels**


- 1) port 2) local devices 3) end devices
- 4) full path 5) cable unique id 6) path unique ID




# And – Which Cabling Topology?



# **Multi-path Options**



## Very Multi-path – Modular Panels



One unit = 48 modules @ 6 LC ports per module = 288 ports

One rack @ 6 Units = 288 modules = 1728 ports


# Very Multi-path – Modular Panels

Device  UK_BIRM_UX01	Port	Patch	PPA Port	Patch Panel A	Back to Back	Patch Panel B	PPB Port	Patch	Port	Device  SW-BHAM-01
Α	23		05	AA		AC	05		NIC 1	В
Room Rack Position Make Model Asset Number IP Address	Speed VLAN	Cable Label Type Length	Speed	Rack Position Make Model	Length	Room Rack Position Make Model	Speed	Colour Cable Label Type Length	Port Type Speed VLAN	Room Rack Position Make Model Asset Number IP Address

Contact Purpose Request date Request Number Project Code / Ref Work number
Path reference
Scheduled date
Installed status
Path length

The spreadsheet data has now grown to up to 60 columns wide!

# And Cabling Extends Beyond The DC






## Define Active Device Naming

#### **Device Name**

- 1) Logical Name
- 2) Type of device / location
- 3) Asset Number

US-SW-DC02-03P Cisco 6509 DC02-B03-U2 Asset HW0078732





Device component – Switch Card US-SW-DCo2-o3P Card3 Cisco 6509 DCo2-Bo3-U2.Sloto3 Asset HWoo78737



Device component – Blade Server UX-NY0445-PROD HP BL685C BLNY05-DC02-B03-U2.Sloto3 Asset HW0078143

# Define Infrastructure Naming



24 Port Copper Patch Panel



288 Port Fibre Panel

#### Patch Panel

AB

Bo<sub>3</sub>-AB

Bo3-5

US-NY-DC05-H1-B03-5

PP Bo3-AB-U5

PP Bo3-AB-U5 to Ho7-AC-U2

PP Bo3-AB-U5 to Ho7-AC-

U2/Ho6-AG-U9

PPC Bo3-AB-U5 to Ho7-AC-

U2:Ports 01 to 24



6 Copper RJ45 Ports




6 Fiber LC Ports

#### **Port Selection**

AB-A Ports 1-6 Ho7-AC-B Ports 7-12 PCI AB-A Ports 1-6 to Ho7-AC-B Port 7-12

AC-03B Ports 1-6 PFI Bo3-AB-03B Ports 1-6 to Ho7-AC-12A Ports 1-6



## Define Infrastructure Naming

- 1. Names and labelling of devices, ports, patch panels are often inconsistent. Keep them as simple as possible.
  - Use external standards if helpful TIA6o6B, TIA942
  - As equipment vendors use various names for ports, decide on your standard
  - Labels and administration identifiers may be different!

```
PP NYC-DC1-RM302-B03-AB-U5 Short code/label PP-AB-U5
```

#### 2. Working practices will dictate when an update is carried out

- Request, design, issue design docs, make change, complete
- A spreadsheet will be locked by one user, so look at a database option

#### 3. But you will need other views / perspective to manage connectivity

Capacity reporting, device views, diagrams

## Case Study Two - Airport



## Scope

**350 Buildings** - Growing to over 400

**Data cabling** - Inside and outside connectivity

**Power** - Equipment rooms / data centres

**Devices** - Anything with data connection

**Step 1** Assess / define standard for naming / schematics

Step 2 Consolidate data and audit where needed

Step 3 Define process and educate on systems and processes

## In Hindsight

## 1. Maybe a spreadsheet wasn't the best way to start...

- It gives structure, but isn't best suited to complex multi-site connectivity
- Loading a database is 4 spreadsheets 1)buildings 2)racks 3)devices 4)connections

# 2. You have to manage inventory and maintain it before you can manage connectivity!

- Inaccuracies in data / naming are often present in other systems
- Without resolving naming issues, audits/ data capture may be wasted

### 3. Managing connectivity has to cope with the real world

- Complex device build – switches, servers, cabling distribution, preterminated cassettes, MPO, blown fibre, diverse paths, etc.



## Understand - Before You Start



Many 1,000s of documents are created by projects, operations and risk processes


## Lists/Database

**Pictures** 

Commercial	Physical	Logical	Business				
Ownership	Room	LAN	System				
Support	Rack	SAN	Service				
Software	Cabling	Virtual Machines	Applications				
Security	Power	OS	User Data				
Contracts	Hardware Build	Remote Mgmt	DR Plan				
Licences	Backup	Environment	Change Impact				
ÜK BIRM_UX01	One Server, Multiple Mappings and Diagrams						

# The Bigger Picture – Think Forward

- Physical locations
- Hardware inventory
- Physical connectivity
- Logical connectivity
- Rack capacity
- Port capacity
- Asset lists
- Project plans
- Work orders
- Alternate paths / SPOF
- Monitoring toolsets



## The More Strategic Approach

## **Physical Changes**

Location and Position
Resource Reservation For Projects
Physical Connectivity
Audits & Manual Data Gathering
Impacts & Dependencies
Adds, Moves & Changes

#### **Trusted Sources**

Discovery Systems
Monitoring Tools
Service Desk CMDB
Spreadsheets – Risk, Contracts
Recovery Plans
Project Handover

References

Updates

**Updates** 

Infrastructure Database(s) & Reporting

Outputs

## **Typical Outputs**

Capacity Management – Space, Power, Connectivity Change Impact Analysis – Impact, Risk, Auditing

Excel



Inventory Extracts
Custom Reporting

Visio



Physical Plans Floor and Rack Diagrams

**Visio** 



Topology Diagrams
Networks, Power, Storage

Visio



System & Architecture Maps ITIL Services, Applications

## In Summary – When?

- Multi-site, multi-technology connectivity management often requires simplification and consistency to be made easy. The normal end goals are speed of change (often reducing cost) and increased control.
- 2. If you document data connectivity of everything that has a data connection, you might as well document power in the same way for data center and power management.
- 3. If you don't manage connectivity, expect frustration and unpredictable project delivery. Be wary of auditors as connectivity shows up internal process gaps. Once control is lost it can be very expensive and time consuming to regain it a connectivity audit!
- 4. Think about the use of specialist tools, rather than Excel or a self developed database.

## Additional Materials +

www.tiaonline.org ANSI/TIA568C, ANSI/TIA606B, ANSI/TIA942

www.bicsi.org ANSI/BICSI-002



www.squaremilesystems.com

Free SMS Visio utilities - Downloads and videos

Webinars/videos - Visio automation, documenting cabling



www.assetgen.com

**Evaluation software** - Free "DCIM/CMS" evaluation version

Webinars - Data centre practices, Visio integration